

Printing date 10.03.2016 Revision: 23.02.2016 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: Aerosol (SM) 1K Spritzspachtel • Article number: REZ312 · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Application of the substance / the mixture: painting \cdot 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Peter Kwasny GmbH Heilbronner Str. 96 D-74831 Gundelsheim Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de · Further information obtainable from: Product safety department · 1.4 Emergency telephone number: Tel.:+49 6269 95 20 · national: National Poisons Information Service, Birmingham Tel.: (0) 12 15 07 55 88/9 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 GHS02 flame Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. GHS07 Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. · 2.2 Label elements · Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labelling: ethyl acetate n-butyl acetate · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H319 Causes serious eye irritation.

(Contd. on page 2)

GB

Page 1/9

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.03.2016

Revision: 23.02.2016

Trade name: Aerosol (SM) 1K Spritzspachtel

	(Contd. of page 1)
H336	May cause drowsiness or dizziness.
· Precautiona	ry statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/eye protection.
P305+P351	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional in	nformation: Without adequate ventilation, explosive atmosphere/gas mix may be created.
\cdot 2.3 Other ha	izards
· Results of P.	BT and vPvB assessment
· PBT: Not ap	plicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:					
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether 🚸 Flam. Gas 1, H220; Press. Gas C, H280	25-50%			
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-XXX	ethyl acetate 🔗 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	25-50%			
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate	5-10%			
• Additional information: For the wording of the listed hazard phrases refer to section 16.					

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- *Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing: If symptoms persist consult doctor.*
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available. (Contd. on page 3)

Printing date 10.03.2016

Revision: 23.02.2016

(Contd. of page 2)

Trade name: Aerosol (SM) 1K Spritzspachtel

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media -

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Cool container whit water
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water. • 6.3 Methods and material for containment and cleaning up:
- b.5 Methods and material for containment and cleaning up: Ensure adequate ventilation.
 Do not flush with water or aqueous cleansing agents
 b.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Take note of emission threshold.
Use only in well ventilated areas.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
· Information about fire - and explosion protection:
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric
lights. Do not pierce or burn, even after use.
· 7.2 Conditions for safe storage, including any incompatibilities
· Storage:
• Requirements to be met by storerooms and receptacles:
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
• Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Protect from heat and direct sunlight.

(Contd. on page 4)

GB

Printing date 10.03.2016

Revision: 23.02.2016

Trade name: Aerosol (SM) 1K Spritzspachtel

(Contd. of page 3)

• 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

•	8.1	Control	parameters
---	-----	---------	------------

- · Ingredients with limit values that require monitoring at the workplace:
- 115-10-6 dimethyl ether
- WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

141-78-6 ethyl acetate

WEL Short-term value: 400 ppm

Long-term value: 200 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

• Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Respiratory protection:

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply. · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- butyl rubber, 0,7mm

· Eye protection:



Tightly sealed goggles

(Contd. on page 5)

Printing date 10.03.2016

Revision: 23.02.2016

Trade name: Aerosol (SM) 1K Spritzspachtel

(Contd. of page 4)

9.1 Information on basic physical a	and chemical properties
General Information	
Appearance: Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. -24 °C
Flash point:	<0 °C Without propellant gas.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	235 °C
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	2.1 Vol %
Upper:	18.6 Vol %
Vapour pressure at 20 °C:	3400 hPa
Density at 20 °C:	$0.75 \ g/cm^3$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	t er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	76.0 %
	With propellant gas. Content given by weight.
Solids content:	24.0 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.

• 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 6)

Printing date 10.03.2016

Revision: 23.02.2016

(Contd. of page 5)

Trade name: Aerosol (SM) 1K Spritzspachtel

- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: Possible in traces.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- Acute toxicity Based on available data, the classification criteria are not met.
- · Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation
- Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
- · 12.5 Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- \cdot European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA

UN1950

(Contd. on page 7)

В —

Printing date 10.03.2016

Revision: 23.02.2016

de name: Aerosol (SM) 1K Spritzspachte	I.
	(Contd. of page
14.2 UN proper shipping name	
ADR IMDC	1950 AEROSOLS
IMDG IATA	AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	AEROSOES, Jummable
ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
2	
Class	2.1
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
	not classified
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Danger code (Kemler):	-
	not classified
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litr Category A. For AEROSOLS with a capacity above 1 litr
	Category B. For WASTE AEROSOLS with a capacity above 1 thr Category B. For WASTE AEROSOLS: Category C, Clea
	of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litr
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4. For AEROSOLS with a capaci
	above 1 litre: Segregation as for the appropria subdivision of class 2. For WASTE AEROSOLS
	Subarvision of class 2. For wASTE AEROSOL. Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
Transport catagory	Not permitted as Excepted Quantity 2
Transport category Tunnel restriction code	2 D
- minut i con tenent cout	~

Printing date 10.03.2016

Revision: 23.02.2016

Trade name: Aerosol (SM) 1K Spritzspachtel						
		(Contd. of page 7)				
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity					
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1					

SECTION 15: Regulatory information


15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

• Technical instructions (air):



· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

- · Department issuing SDS: Product safety department
- · Contact: Hr. Hamberger
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases, Hazard Category 1
- Aerosol 1: Flammable aerosols, Hazard Category 1
- Press. Gas C: Gases under pressure: Compressed gas
- Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

(Contd. on page 9)

[·] Directive 2012/18/EU

Printing date 10.03.2016

Revision: 23.02.2016

Trade name: Aerosol (SM) 1K Spritzspachtel

(Contd. of page 8)

GB

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 • * Data compared to the previous version altered.